

# Spark Plug Application Chart for Evinrude & Johnson Outboards

## 1952 thru 2005

Horsepower	Year	Spark Plug Number (see notes 1 and 2)	Gap (in.)
1.5	1968 - 1970	J6C	.030
2, JR	1971 - 1990	RJ6C	.030
Ultra, Excel 4	1987 - 1988	L78V surface gap or QL77JC4	.030
2.0, 2.3	1991 - 2001	L87YC or QL87YC	.030
2.5	1987 - 1988	QL86C	.030
3	1952 - 1968	J6C	.030
3.3	1991 - 2001	L87YC or QL87YC	.030
3.5	2002 & newer	QL87YC	.030
3, 4, 4 Deluxe	1989 - 2001	QL86C	.030
4	1969 - 1976	J6C	.030
4	1977 - 1987	QL86C or L86C	.030
4	1988	QL77JC4	.030
4, 5 (4-Stroke)	2002 & newer	<b>NGK</b> BPR6ES	.030
4.5	1980 - 1985	QL86C	.030
5	1965 - 1968	J6C	.030
5	1990 - 1997	QL86C	.030
5	1998 - 2001	<b>NGK</b> BPR7HS-10 (see note 1)	.035
5 (4-Stroke)	1997 - 2001	P10Y	.027
5 (4-Stroke)	2002 & newer	<b>NGK</b> BPR6ES	.030
5.5	1954 - 1964	J6C	.030
6	1965 - 1976	J6C	.030
6 (4-Stroke)	1998 - 2001	P10Y	.027
6 (4-Stroke)	2003 - 2004	RP10HC	.027
6 (4-Stroke)	2005 & newer	<b>NGK</b> BPR6ES	.030
6.5 Commercial	1981 - 1993	QL77JC4	.030
7.5	1952 - 1958	J6C	.030
6, 7.5, 8, 8 Commercial	1977 - 2001	QL77JC4 or QL86C	.030
8 (4-Stroke)	1998 - 2001	P10Y	.027
8 (4-Stroke)	2003 & newer	RP10HC	.027
9.5	1964 - 1973	J4C	.030
9.9	1974 - 1976	UL81C	.030
9.9	1977 - 1994	QL77JC4 or QL82C	.030
9.9	1995 & newer	QL82C	.030
9.9 (4-Stroke, 211cc)	1998 - 2001	P10Y	.027
9.9 (4-Stroke, 305cc)	1995 - 2001	RA8HC	.030
9.9 (4-Stroke w/Mikuni Carburetor)	2003 - 2004	<b>NGK</b> DCPR6E (see note 1)	.031
9.9 (4-Stroke w/Keihin Carburetor)	2005 & newer	<b>NGK</b> DCPR6E (see note 1)	.031
10	1952 - 1958	J6C	.030
10	1959 - 1963	J4C	.030
10 Commercial	1992 - 1993	QL77JC4	.030

### NOTES:

1. All spark plugs are Champion brand unless otherwise specified.
2. When more than one plug number appears, the first plug listed is the preferred spark plug.
3. On ALL VRO/OMS equipped motors the "QL" suppressor plug is recommended.

\* This chart was assembled with the latest available Parts Catalogs, Service Manuals and Service Bulletins as of the revision date. If any discrepancies are found, please notify the moderator.

Revised: 2/24/2005

Horsepower	Year	Spark Plug Number (see notes 1 and 2)	Gap (in.)
10, 15 Commercial	1994 - 2001	QL82C	.030
14	1988 - 1989	QL77JC4	.030
14 Commercial	1981 - 1991	QL77JC4	.030
15	1974 - 1976	UL81C	.030
15	1977 - 1992	QL77JC4 (or L78V Surface Gap)	.030
9.9 & 15 Big Bore	1993 - 2001	QL82C	.030
15	1954 - 1956	J6C	.030
15 Commercial	1992 - 1993	QL77JC4	.030
15 (4-Stroke)	1995 - 2001	RA8HC	.030
15 (4-Stroke w/Mikuni Carburetor)	2003 - 2004	<b>NGK DCPR6E</b> (see note 1)	.031
15 (4-Stroke w/Keihin Carburetor)	2005 & newer	<b>NGK DCPR6E</b> (see note 1)	.031
15 (Kerosene)	1995 - 2001	UL77V Surface Gap	
18	1957 - 1973	J4C	.030
18 Jet (25hp powerhead)	1995 - 2001	QL77JC4 or L78V or QL82C	.030
20	1966 - 1973	J4C	.030
25	1952 - 1955	J4C	.030
25	1969 - 1976	J4C	.030
25	1977	QL77JC4 or QL82C	.030
20, 25, 28, 30	1978 - 2001	QL77JC4 or L78V or QL82C	.030
25, 30	2003 & newer	QL77JC4	.030
25, 30 (4-Stroke)	2001 & 200	<b>NGK DCPR6E</b> (see note 1)	.031
25 Commercial	1981 - 2001	QL16V or L16V Surface Gap	
25, 35 (3-Cylinder)	1995 - 2001	QL82C	.030
28	1962 - 1964	J4C	.030
28 Jet (40hp powerhead)	1992 - 2001	QL78YC	.030
30	1956	J6C	.030
33	1965 -1971	J4C	.030
35	1957 - 1959	J6C	.030
35	1976	UL81C	.030
35	1977 - 2000	QL77JC4	.030
35 (3-Cylinder)	1995 - 2001	QL82C	.030
35 Jet (50hp powerhead)	1993 - 2001	QL78YC	.030
E-TEC 40, 50, 60	2004 & newer	QC12PEP	.030
40	1960 - 1973	J4C	.030
40	1974 - 1976	UL81C	.030
40 Commercial (43 cu. in.)	1981 - 1990	UL81C	.030
40 Commercial (45 cu. in.)	1984 - 2001	QL16V Surface Gap	
45, 55 Commercial	1986 - 2001	QL16V or L16V Surface Gap	
50 (V4)	1958 - 1959	J4C	.030
50	1971 - 1975	L77JC4 or QL77JC4	.030
40, 50 (4-Stroke)	1999 & newer	<b>NGK DCPR6E</b> (see note 1)	.031
40, 48, 50 (2-Cylinder)	1980 - 1988	L78V Surface Gap or QL77JC4	.030
40, 48, 50 (2-Cylinder)	1989 - 2001	QL78YC (see note 3)	.030
40, 50	2003 & newer	QL78YC (see note 3)	.030

## NOTES:

1. All spark plugs are Champion brand unless otherwise specified.
2. When more than one plug number appears, the first plug listed is the preferred spark plug.
3. On **ALL** VRO/OMS equipped motors the "QL" suppressor plug is recommended.

\* This chart was assembled with the latest available Parts Catalogs, Service Manuals and Service Bulletins as of the revision date. If any discrepancies are found, please notify the moderator.

Horsepower	Year	Spark Plug Number (see notes 1 and 2)	Gap (in.)
E-TEC 50, 60	2004 & newer	QC12PEP	.030
50 (3-Cylinder)	1995 - 1998	QL78YC (see note 3)	.030
55 (3-Cylinder)	1968 - 1969	L76V Surface Gap or L77JC4	.030
55 (2-Cylinder)	1976 - 1989	L78V Surface Gap or QL77JC4	.030
60 (2-Cylinder)	1980 - 1985	L78V Surface Gap or QL77JC4	.030
60 (3-Cylinder)	1970 - 1971	L76V Surface Gap or QL77JC4	.030
60 (V4)	1964 - 1967	J4C	.030
E-TEC 60	2005 & newer	QC12PEP	.030
60, 70, 75 (49 cu. in.)	1975 - 1989	L77JC4 or QL77JC4	.030
60, 70 (56 cu. in.)	1989 - 1993	L77JC4 or QL77JC4 (see note 3)	.030
60, 70 (56 cu. in.)	1994 - 2001	QL78YC (see note 3)	.030
E-TEC 65 Jet	2005 & newer	QC12PEP	.030
65 Jet (90° crossflow V4)	1992 - 1998	QL77JC4 or QL82C (see note 3)	.030
65 (V4)	1968	L76V Surface Gap or QL77JC4	.030
65 (3-Cylinder)	1972 - 1973	L77JC4	
65 Commercial	1984 - 1987	L78V Surface Gap or L77JC4	.030
65 Commercial	1988 - 2001	QL16V or L16V Surface Gap	
70 (4-Stroke)	1998 - 2001	<b>NGK</b> BPR6ES (see note 1)	.028
60, 70 (4-Stroke)	2002 & newer	<b>NGK</b> BPR6ES (see note 1)	.028
E-TEC 75, 90	2004 & newer	QC12PEP	.030
75 (V4)	1960 - 1965	J4C	.030
80	1966 - 1967	J4C	.030
85	1973 - 1980	L77JC4 or QL77JC4	.030
90	1964 - 1965	J4C	.030
80 Jet (90° crossflow V4)	19xx - 1998	QL77JC4 or QL82C (see note 3)	.030
88, 90, 100, 110, 112, 115	1979 - 1998	QL77JC4 or QL82C	.030
E-TEC 90	2004 & newer	QC12PEP	.030
90, 115 (60° V4 Eagle)	1995 & newer	QL78YC (see note 3)	.030
90, 115 Ficht	1998 - 1999	7712	.030
90, 115 Ficht	2000 & newer	XC12PEPB	.030
90, 115 TurboJet (90° crossflow V4)	1994 - 1997	QL77JC4 or QL82C (see note 3)	.030
90, 115 (4-Stroke)	2003 & newer	<b>NGK</b> BKR6E (see note 1)	.028
100	1966	J4C	.030
100	1967 - 1968	L78V Surface Gap or QL77JC4	.030
100	1971 - 1972	L76V Surface Gap or QL77JC4	.030
100 Commercial	1984 - 1998	L78V or QL16V Surface Gap	
105 Jet (60° V6 Eagle)	1993 & newer	QL78YC (see note 3)	.030
105 Commercial (60° V4 Eagle)	1997 - 2001	QL78YC (see note 3)	.030
115	1969 - 1970	L76V Surface Gap or QL77JC4	.030
115	1973 - 1979	QL16V Surface Gap or QL77JC4	.030
120, 140 (90° V4 Looper)	1985 - 1993	QL77JC4 or QL16V Surface Gap	.030
120, 130, 135, 140 (90° V4 Looper)	1994 - 2001	QL78YC (see note 3)	.030
125	1971 - 1972	L76V Surface Gap or QL77JC4	.030
135, 150, 175 Ficht/DI	2001 & newer	XC12PEPB	.030

## NOTES:

1. All spark plugs are Champion brand unless otherwise specified.
2. When more than one plug number appears, the first plug listed is the preferred spark plug.
3. On **ALL** VRO/OMS equipped motors the "QL" suppressor plug is recommended.

\* This chart was assembled with the latest available Parts Catalogs, Service Manuals and Service Bulletins as of the revision date. If any discrepancies are found, please notify the moderator.

Horsepower	Year	Spark Plug Number (see notes 1 and 2)	Gap (in.)
135, 140	1973 - 1984	UL77V or L16V Surface Gap	
140 (4-Stroke)	2003 & newer	<b>NGK BKR6E</b> (see note 1)	.028
150 Commercial (60° V6 Eagle)	1993 - 2001	QL78YC (see note 3)	.030
150, 175 Ficht/DI	1997 - 1999	7712 (with non-pinned cylinder heads)	.030
150, 175 Ficht/DI	1997 - 1999	XC12PEPB (with pinned cylinder heads)	.030
150, 175 Ficht/DI	2000 & newer	XC12PEPB	.030
150, 155 (90° crossflow V6)	1978 - 1987	UL77V or L16V Surface Gap	
150, 175 (90° crossflow V6)	1988 - 1991	QL77JC4 (see note 3)	.030
155 Commercial	1989 - 1992	QL16V Surface Gap	
175, 185	1977 - 1987	UL77V or QL16V Surface Gap	
185 Commercial	1990 - 1993	QL16V Surface Gap or QL77JC4	.030
E-TEC 200, 225, 250 (incl. HO)	2005 & newer	<b>QC10PEPB</b>	.030
200, 225 (4-Stroke)	2004 & newer	<b>NGK BKR6E</b> (see note 1)	.028
200	1976 - 1983	UL77V or QL16V Surface Gap	
200, 225	1986 - 1993	QL77JC4	.030
200, 225, 250 Ficht/DI (incl. HO)	1999 & newer	QC12PEP	.030
200 Commercial	1992	QL16V or L16V Surface Gap	
200 Commercial	1993 - 2001	QL78YC (see note 3)	.030
200, 225, 225HO	1994 - 2001	QL78YC (see note 3)	.030
225, 250 Ficht/DI (incl. HO)	1999 & newer	QC12PEP	.030
E-TEC 225, 250 (incl. HO)	2005 & newer	<b>QC10PEPB</b>	.030
235	1978 - 1985	QL16V or UL77V Surface Gap	
250 Ficht/DI	1999 & newer	QC12PEP	.030
250, 275, 300 (V8)	1985 - 1998	QL78YC (see note 3)	.030
E-TEC 250	2005 & newer	<b>QC10PEPB</b>	.030
225 (4-Stroke)	2004 & newer	<b>NGK BKR6E</b> (see note 1)	.028
OMC Sea-Drive 2.5, 26 Litre	1988 - 1992	UL77V	
OMC Sea-Drive 1.6, 1.8, 2.0, 2.7, 3.0 Litre	1988 - 1992	QL77JC4 (see note 3)	.030
OMC Sea-Drive 3.6, 4.0 Litre	1988 - 1992	QL77JC4 (see note 3)	.030
OMC Sail-Drive (Zepher)	1977 - 1984	QL8YC	.045

## NOTES:

1. All spark plugs are Champion brand unless otherwise specified.
2. When more than one plug number appears, the first plug listed is the preferred spark plug.
3. On **ALL** VRO/OMS equipped motors the "QL" suppressor plug is recommended.

\* This chart was assembled with the latest available Parts Catalogs, Service Manuals and Service Bulletins as of the revision date. If any discrepancies are found, please notify the moderator.